

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT):

(51) International Patent Classification 6 : C12M 1/30, A61B 10/00, B01L 3/00		A1	(11) International Publication Number: WO 99/31218
			(43) International Publication Date: 24 June 1999 (24.06.99)
(21) International Application Number: PCT/GB98/03669		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 10 December 1998 (10.12.98)			
(30) Priority Data: PCT/GB97/03458 16 December 1997 (16.12.97) GB 9813127.9 17 June 1998 (17.06.98) GB			
(71) Applicant (for all designated States except US): CELSIS INTERNATIONAL PLC [GB/GB]; Cambridge Science Park, Milton Road, Cambridge CB4 4FX (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): COOKE, Anthony [GB/GB]; 12 Dunstal Field, Cottenham, Cambs. CB4 4UH (GB). PIRZAD, Ramin [GB/GB]; 40 Nursery Gardens, St. Ives, Cambs. PE17 6NL (GB).			
(74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).		Published With international search report.	

(54) Title: SAMPLE-COLLECTING AND ASSAY DEVICE

(57) Abstract

An assay device comprises a tube (1), a removable top part (3) and a bottom part (4), wherein an elongate member (6) with a swab (7) at its distal end is mounted on the top part, the top part includes a compartment (8) containing liquid and partly defined by a first frangible membrane (9) that can be ruptured to release the liquid into the tube, and the bottom part contains a reagent and is partly defined by a second frangible membrane that can be ruptured on movement of the bottom part relative to the tube. Reaction occurring in the bottom part can be observed through a window (10).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 99/31218

PCT/GB98/03669

1

SAMPLE-COLLECTING AND ASSAY DEVICE

Field of the Invention

This invention relates to a sample-collecting and assay device, and in particular to a simple hygiene monitor.

5 Background of the Invention

WO-A-9425619 describes reactions where metabolites such as ATP can be amplified and detected, e.g. colorimetrically. Application of this chemistry is of value in dirt monitoring or in the detection of microorganisms on a surface that are collected by swabbing.

10 WO-A-9525948 discloses a sample-collecting and assay device comprising a tube, a removable top part and a bottom part, wherein an elongate member with a swab at its distal end is mounted on the top part. There may be one or more foil-sealed bottom parts fixed within the tube, and the foils are successively broken by movement of the swab, or a coaxially-extending blade-like member, through the tube.

15 WO-A-9703209 discloses a similar device, in which reagent is contained in a bottom part with a window, and which has a seal broken by movement of the swab through the tube. Another similar device is disclosed in WO-A-9723596.

Summary of the Invention

20 An assay device according to the present invention is for use in determining the presence in a liquid sample of a target component that, in combination with other components, undergoes a reaction to give a detectable signal. The novel device comprises a tube, a removable top part and a bottom part, wherein an elongate member with a swab at its distal end is mounted on the top part, the top part includes a compartment containing liquid and partly defined by a first frangible membrane that can
25 be ruptured to release the liquid into the tube, and the bottom part contains a reagent and is partly defined by a second frangible membrane that can be ruptured on movement of the bottom part relative to the tube.

By means of the invention, direct analysis can be made, by observing the signal generated, in the bottom part. Although the novel device shares many characteristics
30 with the prior art devices, described above, its particular advantages include the use of a syringe-like mechanism within the top dispenser, to ensure repeatable and reproducible dispensing of liquid reagent. Although the top part may be unitary or comprise a

WO 99/31218

PCT/GB98/03669

2

separate component containing reagent, the design of the top reagent container and its holder may be such that a single operation, depressing the container, ruptures the seal and evacuates the contents of the container down the swab shaft, ensuring accurate and reproducible dispensing of the liquid reagent with minimal dead volume and without introduction of any air, unlike a "pumping" dispensing system.

Description of the Invention

A device of this invention is particularly suitable for determining the presence of microorganisms, in which case the target component is ATP. The invention will now be described by way of example only with reference to this embodiment.

Further, again for the purpose of illustration, the invention will be described with reference to reactions of the type described in WO-A-9425619, i.e. involving enzymes and their substrates. These materials constitute the components that, in combination, undergo the reaction that gives the detectable signal. Such a reaction includes the following:



wherein G is glucose and G6P is glucose-6-phosphate. These reactions are catalysed by adenylate kinase and glucokinase. Glucose is then converted to give a colour, in a further enzymatic sequence, e.g. utilising glucose oxidase (GO) and horseradish peroxidase (HRP).

Alternatively, the analyte may be detected by bioluminescence. Suitable reagents etc. are described in WO-A-9525428.

The reaction components may be present together in the bottom part, in a freeze-dried mixture.

In use of a device of the invention, a sample, e.g. of microorganisms obtained by swabbing, is provided and the reagents and liquid are mixed with them. Especially if the reaction generates a colour, comparison of that and a standard can be made readily, to give a quick indication of the concentration of the analyte in the sample.

The invention will now be described by way of example only with reference to the accompanying drawings, in which:

Figure 1A shows separate side views of a device embodying the invention, and Figure 1B is a cross-section of the same embodiment, along the line A-A in Fig. 1A; and

WO 99/31218

PCT/GB98/03669

3

Figure 2 is an exploded view of the embodiment shown in Fig. 1.

For simplicity, a device of the invention will be described with reference to Fig. 1B. The embodiment illustrated there comprises a tube 1 with a pen-type holder 2. A top part 3 and a bottom part 4 are each mounted on the tube and each can be pushed into
5 close engagement with the tube. In the case of the top part, close engagement is prevented, until required, by the removable or peelable safety seal 5.

The top part 3 has mounted thereon a tubular elongate member 6 that terminates in a swab 7. The top part 3 also comprises a separate component 8 which is a compartment having a foil seal 9. On depression of this component, by a simple syringe
10 action, without pumping, the foil seal is ruptured, and a known amount of liquid is discharged down the elongate member to the swab 7, within the tube 1. The top end of the elongate member is a sliding fit within the component 8.

The bottom part 4 is in the form of a foil-sealed cuvette including a window 10. It may contain freeze-dried reagent(s). The foil is broken by pushing the part 4 inwardly
15 with respect to the tube 1. The foil may be broken on the swab or on an angled blade-like member 11 provided as an internal component of the tube 1.

In use, the top part 3 is removed from the tube 1, a sample is taken up on the swab 7, and this is replaced in the tube. The seal on the bottom part 4 is then broken. The safety seal 5 is then removed, and the component 8 pushed inwards, to release a
20 known quantity of liquid. Results can be read through the window 10. A qualitative assessment can be made by comparison of the colour generated with reference spots of different colour intensity (of which three are shown in Fig. 1A).

Various modifications to the illustrated device may be made, within the scope of the invention. For example, the proximal end of the elongate member 6 may be longer,
25 so that it extends to a greater extent into the component 8, when that is depressed, so that there is a smaller residual volume. That volume may be accurately predetermined, e.g. 50 μ L. That in turn ensures that for a given volume of liquid in the component 8, e.g. 500 μ L, a predetermined amount is accurately dispensed, *via* the elongate member, to the swab.

30 A further modification involves, instead of the seal 5, a frangible connection between the two pieces of the top part. This allows the whole of the top part to be used in swabbing; when replaced on the tube, breakage of the frangible connection allows

relative movement of the two pieces of the top part, to release the liquid. Preferably, the top part and the tube comprise means for their mutual location, e.g. a tongue and groove. It is also preferred that the frangible connection between the two pieces of the top part should be broken by relative rotation, i.e. in a sense different to that in which movement
5 releases the liquid. This is also assisted by the mutual location of the top part and the tube.

When the seal on the component in the top part is broken, liquid (i.e. extractant/buffer) surrounds sample that has been collected on the swab. When the seal on the bottom part is then broken, simple shaking allows the sample to be removed from
10 the swab as well as activating reagent in the bottom part. This assists the quantitative nature of the analysis.

WO 99/31218

PCT/GB98/03669

5

CLAIMS

1. An assay device comprising a tube, a removable two-piece top part and a bottom part, wherein an elongate, tubular member having a swab at its distal end is mounted on one piece of the top part, wherein the other piece of the top part includes a compartment
5 containing liquid and partly defined by a first frangible membrane that can be broken, by relative movement of the two pieces, to release the liquid into the tubular member, and wherein the bottom part contains a reagent and is partly defined by a second frangible membrane that can be broken on movement of the bottom part relative to the tube.
2. A device according to claim 1, wherein the bottom part comprises a window, for
10 observation of a reaction therewithin.
3. A device according to claim 1 or claim 2, wherein the proximal end of the tubular member is a sliding fit within the compartment, on the relative movement thereof.
4. A device according to any preceding claim, wherein the two pieces of the top part are frangibly connected, whereby breakage of the connection allows said relative
15 movement of the two pieces.
5. A device according to claim 4, wherein the frangible connection is broken by relative rotation of the two pieces.
6. A device according to any preceding claim, wherein the top part and the tube comprise respective means for their mutual location.

WO 99/31218

PCT/GB98/03669

1/3




FIG. 1A

WO 99/31218

PCT/GB98/03669

2/3




FIG. 1B

WO 99/31218

PCT/GB98/03669

3/3




FIG. 2

INTERNATIONAL SEARCH REPORT

ational Application No

PCT/GB 98/03669

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C12M1/30 A61B10/00 B01L3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 96 14570 A (IDEXX LAB INC) 17 May 1996 see page 3, line 25 - line 26 see page 4, line 10 - line 14 see page 10, line 9 - line 29; figure 3A see page 11, line 2 - line 34; figures 5C,6 ---	1
Y	EP 0 538 891 A (FUJISAWA PHARMACEUTICAL CO) 28 April 1993 see column 1, line 33 - line 50; figure 11 see column 5, line 2 - line 24 ---	1
A	WO 93 00994 A (AMERSHAM INT PLC) 21 January 1993 see page 3, line 1 - line 21; figure 1 --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

23 March 1999

Date of mailing of the international search report

31/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hocquet, A

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/03669

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 03209 A (CHARM SCIENCES INC ;SKIFFINGTON RICHARD (US); ZOMER ELIEZER (US)) 30 January 1997 see page 6, line 2 - line 16; figures 2-5 see page 20, line 26 - line 28; figure 5G ----	1,2
A	US 4 178 930 A (FISHER FRANK R JR) 18 December 1979 see column 3, line 3 - line 8 ----	4
A	US 4 508 534 A (GARVER SR EDWARD B ET AL) 2 April 1985 see column 7, line 47 - line 68; figures 5,6 ----	5
P,X	WO 98 27196 A (COOKE ANTHONY ;CELSIS INT PLC (GB); PIRZAD RAMIN (GB)) 25 June 1998 see the whole document ----	1-3
A	WO 93 12421 A (NASON FREDERIC L) 24 June 1993 see page 11, paragraph 2 see page 12, paragraph 2 - page 13, paragraph 1; figures 7-9 ----	1,2
A	US 5 084 245 A (BERKE CARL M ET AL) 28 January 1992 see column 14, line 28 - line 54; figures ----	2
A	US 4 353 868 A (JOSLIN JOEL A ET AL) 12 October 1982 see column 3, line 1 - line 35; figures see column 3, line 63 - column 4, line 10 see column 5, line 11 - line 18 ----	1
A	WO 95 25948 A (CELSIS INT PLC ;FOOTE NICHOLAS PETER MARTIN (GB); GRANT PETER LEON) 28 September 1995 cited in the application see page 2, line 13 - line 15 see page 7, line 8 - line 18 -----	2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/03669

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9614570 A	17-05-1996	NONE	
EP 0538891 A	28-04-1993	JP 2630185 B JP 5192377 A KR 9605814 B US 5352191 A	16-07-1997 03-08-1993 01-05-1996 04-10-1994
WO 9300994 A	21-01-1993	AT 137140 T CA 2112672 A DE 69210239 D DE 69210239 T DK 592503 T EP 0592503 A ES 2087540 T JP 7500049 T US 5449494 A	15-05-1996 21-01-1993 30-05-1996 10-10-1996 01-07-1996 20-04-1994 16-07-1996 05-01-1995 12-09-1995
WO 9703209 A	30-01-1997	AU 4756896 A CA 2226857 A EP 0861330 A	10-02-1997 30-01-1997 02-09-1998
US 4178930 A	18-12-1979	NONE	
US 4508534 A	02-04-1985	US 4402682 A AR 229193 A AU 564874 B AU 1040183 A BR 8208002 A CA 1184461 A DE 3278875 A EP 0095477 A WO 8301901 A	06-09-1983 30-06-1983 27-08-1987 17-06-1983 18-10-1983 26-03-1985 15-09-1988 07-12-1983 09-06-1983
WO 9827196 A	25-06-1998	AU 7738598 A	15-07-1998
WO 9312421 A	24-06-1993	CA 2075193 A US 5266266 A EP 0515398 A EP 0572637 A WO 9210136 A US 4978504 A US 5078968 A US 5238649 A	14-06-1992 30-11-1993 02-12-1992 08-12-1993 25-06-1992 18-12-1990 07-01-1992 24-08-1992
US 5084245 A	28-01-1992	NONE	
US 4353868 A	12-10-1982	NONE	
WO 9525948 A	28-09-1995	AU 1955595 A	09-10-1995

THIS PAGE BLANK (USPTO)